




STANDARD STROBE



MODEL TYPES ::

- LP > Short standard strobe (2 watt)
- LT > Tall standard strobe (5 watt)

FEATURES ::

- Bright light with low power consumption
- 500 mm (19.6 in) PVC jacketed leads
- Transient voltage and reverse polarity protection
- Multi-voltage (10-100 VDC, 20-72 VAC), 110 and 220 AC models
- LP: 2 Watt output; LT: 5 Watt output (.5 and 1 watt available upon request)
- IP67 rated (fully weatherproof), gasket included
- All models are CE compliant
- 12 month guarantee



ACCESSORIES + OPTIONS ::

- Sealed mounting box for LP (FX1)
- Base mount with screw terminals (FX2)
- Wall mount bracket with screw terminals (FX40)



ORDERING INFORMATION ::

MODEL TYPE:: LP1X, LT2X
 VOLTAGE:: MV (10-100 VDC, 20-72 VAC), 110, 220
 WATTAGE:: LP:/2 LT:/5
 COLOR:: red, amber, green, blue, clear
 EXAMPLE:: LP1X-MV/2-1R [short strobe, multi-voltage, red]

VOLTAGE	CURRENT LP	CURRENT LT
12V	130	255
24V	95	190
110V AC	25	60
220V AC	15	30

DIMENSIONS

