

## LED INDUSTRIAL STROBE

### LT-LED Dual Green Continuous, Red Strobe



CE – certified to EMC directive 2004/108/EC.  
 Complies with low voltage directive 2006/95/EC.  
 High voltage transient and polarity reversal protected.  
 Operating temperature: -20°C to + 55°C.



LT1X110/230V DUAL	red >10cd green >3cd	65 flashes/min 6 bursts/flash (red only)	85–265 Vac	IP67	158gms
LT1XMV/LED DUAL			10–100Vdc		

#### Features:

A compact dual function LED beacon - green continuous and red flashing light.

- Multivoltage 10–100Vdc, and 110Vac and 230Vac versions
- Ideal for indicating process/system status – green continuous light for normal operation, red flashing to indicate status change
- A unique low cost alternative to conventional tower beacons
- Clear lens with colored LEDs
- Low power consumption
- 3 year guarantee
- Weatherproof to IP67

#### Materials:

Polycarbonate lens and base. ROHS compliant.

#### Accessories:

**FX2**  
mounting  
base



**FX40**  
mounting  
bracket



**FX39**  
mounting  
pole



**Actual Hole 5mm  
Hole to Hole 55mm  
70mm Diameter Base**

Product	<i>i</i> red flashing	<i>i</i> green constant	Red / Green	
LT1X110/230V DUAL	15mA @ 110Vac 10mA @ 230Vac		-R	-G
LT1XMV/LED DUAL	110mA @ 12Vdc 55mA @ 24Vdc 35mA @ 50Vac 25mA @ 100Vac	80mA @ 12Vdc 40mA @ 24Vdc 25mA @ 50Vac 20mA @ 100Vac	-R	-G

  

3 x 5.5mm holes