



MODEL TYPES ::

- STL** > Continuous LED light
- STLB** > Continuous LED light with audible alarm (83dB at 1M)
- STLF** > Continuous and flashing LED light
- STLZ** > Continuous and flashing LED light with audible alarm (83dB at 1M)

STANDARD SERIES LED TOWER LIGHTS

FEATURES ::

- ▶ Pre-wired and pre-assembled with 300mm pole, nuts and right angle bracket (NT100)
- ▶ 24 LEDs per red, amber + green sections and 12 LEDs per blue + white
- ▶ Lenses are heat and shock resistant polycarbonate resin
- ▶ Prism-cut, 12-sided lens design provides superior light diffusion
- ▶ Continuous and flashing (80FPM) functions in STLF and STLZ
- ▶ IP20 rated (dust resistant)
- ▶ All models are CE compliant
- ▶ Standard color sequence: 1: red, 2: red-green, 3: red-amber-green, 4: red-amber-green-blue, 5: red-amber-green-blue-white



ACCESSORIES + OPTIONS ::

- ▶ Flange mount base for pole (NT-150)
- ▶ Wall mount base (NT-160)
- ▶ Custom lens color sequence
- ▶ Custom pole lengths to 1 meter (STS-1M)
- ▶ Rotating (180°) base (NT-170)
- ▶ Flange-mounted base available (STLR)



ORDERING INFORMATION ::

MODEL TYPE:: STL, STLB, STLF, STLZ
 VOLTAGE:: 12, 24, 110, 220
 NUMBER OF LIGHTS:: 1, 2, 3, 4, 5
 EXAMPLE:: STL-24-3 [continuous, 24V, DC, 3-light]

RATED VOLTAGE	CURRENT
12V DC	80 mA
24V DC	40 mA
110V AC	20 mA
220V AC	15 mA
AUDIBLE	15 mA

DIMENSIONS

▶NT100

▶STL/STLB WIRING CONNECTIONS ▶STLF/STLZ

